

3M PRODUCT DATA SHEET

Date of Issue: 06/2004

Product Title

Scotch® Tape 2328 – Autograde Masking Tape

Product Description/Markets

Scotch Tape 2328 is a chamois coloured creped paper masking tape suitable for a wide variety of applications in the refinishing market.

Construction/Physical Properties

Thickness:	0.135 mm	AFERA 4006
Adhesion to steel:	6.5N/25 mm	AFERA 4001
Tensile strength:	88N/25 mm	AFERA 4004
Elongation:	10%	AFERA 4005
Temperature performance:	80°C	

Applications

Scotch Tape 2328 will perform satisfactorily within a range of temperatures from ambient to 80°C in many applications in the refinishing market.

Sizes Available/Conversions

Width (mm):	15, 19, 25, 30, 38, 50, 75 and 100
Length (m):	50

Product Highlights

Features	Advantages	Benefits
Latex saturated creped paper backing	Conformability	Good curve masking
	Thinness	Good paint line
	Solvent resistance	Prevents bleed through
	Easy hand tear	Good handling
	Good paint anchorage	Good paint flaking resistance
	Sliver resistance	Easy removal
Crosslinked rubber resin adhesive	Instant adhesion	Sticks easily
	Good holding power	Resists lifting

Storage & Shelf Life

Store in a clean dry place. Temperature of 21°C and 50% relative humidity are recommended

Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.

3M Automotive Aftermarkets Division

3M Atherstone
Ratcliffe Road
Atherstone
Warwickshire
United Kingdom
Tel: ++44-1827-710292
Fax: ++44-1827-710393