# **3M** Multi Gas/Vapor Cartridges

Issue Date 9/1/09

## **Cartridge Selection Simplified**

3M<sup>™</sup> Multi Gas/Vapor Cartridges combine the protection offered by five different cartridges into one simple-to-use cartridge.

#### Simplicity

3M multi gas/vapor cartridges help:

- Simplify cartridge selection and respirator training.
- Reduce inventory costs.

3M multi gas/vapor cartridges are also available with permanently attached P100 filters.

#### Versatility

The multi gas/vapor cartridges can be used with a variety of 3M facepieces:

• 3M<sup>™</sup> Half Face and Full Facepieces 6000, 7000 and Ultimate FX FF-400 Series.

#### Protection

- 3M multi gas/vapor cartridges are NIOSH approved for ten types of contaminants:
- Organic Vapors
- Chlorine
- Hydrogen Chloride
- Sulfur Dioxide
- Hydrogen Fluoride
- Chlorine Dioxide
- Hydrogen Sulfide
- Ammonia
- Methylamine
- Formaldehyde

- Cartridges offer protection against a wide range of contaminants found in many different industries, including:
  - Petrochemical and chemical processing
  - Utilities
  - Mining
  - Pulp and paper manufacturing
  - Pharmaceuticals



These cartridges help protect against certain airborne contaminants. **Misuse may result in sickness or death.** Before use, the wearer must read and understand *User Instructions* provided as a part of product packaging. Time use limitations may apply. For proper use, see package instructions, supervisor or call 3M OH&ESD Technical Service in U.S.A., 1-800-243-4630. In Canada, call 1-800-267-4414.

Additional use instructions, product limitations, approval labels, and warnings are included with each facepiece and filter package.



3M<sup>™</sup> Multi Gas/Vapor Cartridges shown with 3M<sup>™</sup> Full Facepiece 6000 Series and 3M<sup>™</sup> Organic Vapor Monitor 3510.

#### **Ordering Information**

	Product Number	Description	Quantity
	6006	Multi gas/vapor cartridge	60/case
	60926	Multi gas/vapor—P100 cartridge	60/case
3M <sup>™</sup> Multi gas/vapor Cartridges are approved for use with the 3M <sup>™</sup> 6000, 7000 and Ultimate FX FF-400 Series Facepieces.			

All multi gas/vapor cartridges/filter assemblies can be used up to the NIOSH approval limits:

- 10 times the permissible exposure limit (PEL) with half facepiece, or
- 10 times the PEL with full facepiece qualitatively fit tested, or
- 50 times the PEL with full facepiece quantitatively fit tested, or
- the maximum use concentration allowable in applicable OSHA standards, whichever is lower.

#### Important

Before using these filters, you must determine the following:

- 1. The type of contaminant(s) for which the respirator is being selected.
- 2. The concentration level of contaminant(s).
- 3. Whether the respirator can be properly fitted on the wearer's face. Do not use with beards, on other facial hair, or other conditions that prevent a good seal between the face and the faceseal of the respirator.
- 4. Before use of these respirators, a written respiratory protection program must be implemented, meeting all the requirements of OSHA 29 CFR 1910.134, including training, medical evaluation and fit testing.

For more information, please contact:

#### 3M Occupational Health and Environmental Safety Division (OH&ESD)

In the U.S., contact: Customer Service 1-800-328-1667 Technical Assistance 1-800-243-4630 Website www.3M.com/OccSafety For other 3M products 1-800-3M HELPS

#### In Canada, contact:

3M Canada Company, OH&ESD P.O. Box 5757 London, Ontario N6A 4T1 **Customer Care** 1-800-364-3577 **Technical Assistance (Canada only)** 1-800-267-4414

Website www.3M.ca/safety

Technical Assistance In Mexico 01-800-712-0646 5270-2255, 5270-2119 (Mexico City only) Technical Assistance In Brazil 0800-132333

### **3**M

**Occupational Health and Environmental Safety Division** 3M Center, Building 235-2E-91 St. Paul, MN 55144-1000