



Scotch-Brite™
EXL-XP Deburring Wheels

The background of the central section features three large, grey, circular deburring wheels arranged in a row, overlapping from left to right. To the right of the wheels, a gloved hand is shown using a metal part with several holes, which is being deburred against one of the wheels. The background is a collage of various shades of blue, green, and purple.

Superior Deburring Evolved

Discover the new Scotch-Brite™ EXL-XP Deburring Wheel which can provide exceptional long life, conformability and smooth operations in the most demanding deburring applications



Even after 50 years...

3M is one of the industry's leaders in surface conditioning wheels, continually improving and adding to its evolving convolute deburring wheel line. The new Scotch-Brite™ EXL-XP Deburring Wheel is the latest addition to this family.

▶ Ultimate Durability

Scotch-Brite™ EXL-XP Wheels can offer superior durability and edge retention for tough burrs and sharp edges. Using new technology that retains wheel conformability, this wheel can offer high cut rate, long life and smooth running.

▶ Superior Finish

Delivering excellent finishes is not a problem for the Scotch-Brite™ EXL-XP Wheel when tackling tough burrs. This wheel still offers the same superior finish and consistency that customers have come to expect from the Scotch-Brite™ EXL family of wheels.

▶ Maximum Consistency

The unique resin system and convolute construction allows the EXL-XP Wheel to run smooth and consistent while keeping the mineral exposed to do the work. The conformability of the EXL-XP can help resist “chunking” so your wheel continues to run true, even with the higher density variations.

Scotch-Brite™

EXL-XP Deburring Wheel Product Availability

Grade	Size	3M ID or Part Number	UPC Number	Qty.
EXL-XP EXL Deburring Wheel, 9S FIN	6" x 1/2" x 1"	61-5002-9349-5	00-048011-60442-8	4
	6" x 1" x 1"	61-5002-9223-2	00-048011-60306-3	3
	8" x 1/2" x 3"	61-5002-9350-3	00-048011-60443-5	4
	8" x 1" x 3"	61-5002-9224-0	00-048011-60307-0	3
	8" x 2" x 3"	61-5002-9351-1	00-048011-60444-2	2
	12" x 1/2" x 5"	61-5002-9352-9	00-048011-60445-9	2
	12" x 1" x 5"	61-5002-9225-7	00-048011-60308-7	1
EXL-XP EXL Deburring Wheel, 10S FIN	12" x 2" x 5"	61-5002-9353-7	00-048011-60446-6	1
	6" x 1/2" x 1"	61-5002-9354-5	00-048011-60447-3	4
	6" x 1" x 1"	61-5002-9226-5	00-048011-60310-0	3
	8" x 1/2" x 3"	61-5002-9355-2	00-048011-60448-0	4
	8" x 1" x 3"	61-5002-9227-3	00-048011-60311-7	3
	8" x 2" x 3"	61-5002-9356-0	00-048011-60449-7	2
	12" x 1/2" x 5"	61-5002-9357-8	00-048011-60450-3	2
EXL-XP EXL Deburring Wheel, 11S FIN	12" x 1" x 5"	61-5002-9228-1	00-048011-60312-4	1
	12" x 2" x 5"	61-5002-9358-6	00-048011-60451-0	1
	6" x 1" x 1"	61-5002-9229-9	00-048011-60315-5	3
	6" x 1/2" x 1"	61-5002-9359-4	00-048011-60452-7	4
	8" x 1/2" x 3"	61-5002-9360-2	00-048011-60453-4	4
	8" x 2" x 3"	61-5002-9361-0	00-048011-60454-1	2
	12" x 1" x 5"	61-5002-9231-5	00-048011-60317-9	1
	12" x 2" x 5"	61-5002-9362-8	00-048011-60455-8	1
	12" x 1/2" x 5"	61-5002-9363-6	00-048011-60456-5	2
	8" x 1" x 3"	61-5002-9230-7	00-048011-60316-2	3

Your new Scotch-Brite™ EXL-XP Wheel can benefit and optimize your operation as follows:

- Easy on the operator because it requires less pressure
- Consistent finish throughout the life of the wheel
- Exposed mineral results in less smearing
- Less frequent dressing as the wheel wears consistently and stays smooth
- Higher throughput from a fast cutting wheel
- Wheel durability reduces abrasive cost

Product Use: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



**Industrial Business
Customer Response Center**

900 Bush Avenue,
Building 21-1W-10
St. Paul, MN 55106

Please recycle. Printed in U.S.A.
© 3M 2008. All rights reserved.
61-5002-8218-3

3M and Scotch-Brite are
trademarks of 3M.