

3M™ Sandpaper 216U Soft Hand



Product Construction

<i>Mineral</i>	Aluminum oxide
<i>Bonding</i>	Resin bond.
<i>Backing</i>	Paper – A weight
<i>Grit Range</i>	150-180-220-240-280-320-360-400-500-600-800
<i>Size</i>	114 mm x 25 mt

Available Forms



f

Applications

Materials:
Used for hand of lacquers, paints, plastics and funds

f

Recommendation

Recommended for hand working

f

f

f

f

3M™ Sandpaper 216U Soft Hand

Features

Aluminum oxide

Paper backing

Double resin bond

Additive

Advantages

Cut accuracy

Excellent flexibility and mechanical strength

More aggressive and longer life

High resistance

Benefits

High quality

Higher duration and more consistent cut

High productivity

Longer life

Machines



Safety



Quality

3M Plants are ISO 9002 certified.

Product Use: All statements, technical information and recommendations contained in this document are based on tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.



3M Italia SpA
Reperto ASD Abrasivi Industriali

Via Norberto Bobbio,21
20069 – Pioltello Milano
Tel: 02 7035 2529

Fax: 02 93660172

Data Sheet: Sandpaper 216U Soft Hand
Issued 06/11

© 3M 2011. All rights reserved.