3M<sup>™</sup> Scotch-Weld<sup>™</sup> Structural Adhesive Primers EW-5000 and EW-5000 AS



## 3M<sup>™</sup> Scotch-Weld<sup>™</sup> Structural Adhesive Primers EW-5000 and EW-5000 AS

are a pair of water-based, low volatile organic compounds (VOC) structural bonding primers, which provide comparable performance to traditional solvent-based options.

- Excellent corrosion protection
- Robust mechanical performance
- Impressive hot/wet durability
- Serves both 250° and 350°F cure requirements
- Sprayable and brushable application

Minimize VOC Impact Improve Productivity Reduce Wastes Helps lower costs



## 3M<sup>™</sup> Scotch-Weld<sup>™</sup> Structural Adhesive Primers EW-5000 and EW-5000 AS

**3M™ Scotch-Weld™ EW-5000 and EW-5000 AS Primers** significantly reduce VOC emissions and the EW-5000 AS primer contains no hexavalent chromium. Additionally, the primers can help improve production rates by offering high transfer efficiency and quick flash off for no wait time between passes. Let 3M's unparalleled technical service and support show you how water-based primers can make a difference to your primer line and your bottom line.

3M <sup>™</sup> Scotch-Weld <sup>™</sup> Structural Adhesive Primer	Size	3M ID Number	
EW-5000	Quart	62-3963-6545-4	Qualified to BMS 5-89 and BMS 5-137 Meets SCAQMD Rule 1124 VOC Limits for Primers
	1 Gallon	62-3963-8541-1	
	5 Gallons	62-3963-8545-2	
EW-5000 AS	1 Quart	87-2500-0100-2	Meets SCAQMD Rule 1124 VOC Limits for Primers and OSHA 29 CFR 1910.1026
	1 Gallon	87-2500-0102-8	
	5 Gallons	87-2500-0101-0	

Compatible with HVLP and conventional spray units.

## See 3M Scotch-Weld Structural Adhesive Primers EW-5000 and EW-5000 AS in action at 3M.com/aerospace.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Aerospace and Aircraft Maintenance Department Building 223-1N-14 St. Paul, MN, 55144-1000 Phone 1-800-235-2376 www.3m.com/aerospace

3M and Scotch-Weld are trademarks of 3M.

Please recycle. Printed in USA. Blgr. 11080246 © 3M 2011. All rights reserved. 60-9700-0306-1