

General Rules for Shelf Life Statements

	Product	Shelf Life	Storage Conditions
1	Semi-Finished Goods (Materials or products sold in a bulk or semi-finished state.)	Not determined	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
2	Hard Goods inside of kits (metals, plastics, glass components and tools)	Not determined	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
3	OEM Tapes		
	All (except 40)	5 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
	40 Tape	2 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
4	Vinyl Tapes, Rubber Tapes	5 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
5	Heat Shrink		
	BBI-A, EPS, FP, HDT, MDT, MFP, MW, SFTW, VFP	10 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
	Molded Shapes, VTN, NST, HDBB	5 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
	PSTH	4 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
6	Adhesives, Cleaning Products	2 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
7	EPDM Products (including Cold Shrink)	5 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
8	Silicone Cold Shrink Products		
	Low and medium voltage	3 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
	69 kV Splices	1 year from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
	69kV Terminations	3 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
	145 kV Termination and Splices	2 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
9	Neoprene Cold Shrink Products	2 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
10	Cable Ties	5 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
11	Terminals, Connectors	5 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
12	Mastics	5 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
13	Insulating Sealers	1 year from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
14	Wire Marking and Identification Products	2 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
15	Portable Labeler cartridges	18 months from date of shipment	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)

General Rules for Shelf Life Statements

	Product	Shelf Life	Storage Conditions
16	Resins		
	Electrical Insulating Resins: 4, 2131, 2136, CRC	3 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
	2100, 2104, 2123, 3570G-N, 5136N	2 years from date of mfg	
	OEM Liquid Resins: 3, 5, 8, 9, 10, 208, 209, 210, 226, 235, 241, 250, 251, 252, 253, 255, 280, 281, 282, MR283FO75	2 years from date of mfg	Humidity controlled storage (10C/50F to 27C/80F & <75% RH)
	Pipe Coatings: 206N*, 207R, 226N+, 626, 6171*, 6233, 6233P, 6258, 6259, 6352*, 6352HF	12 months from date of mfg *24 months from date of mfg	Maintain < 80F *Maintain < 65F
	134, 135	18 months from date of mfg	Maintain < 80F
	Liquid Coatings: 345*	3 months from date of mfg *12 months from date of mfg	Maintain < 70F *Maintain < 50F
	323/323i, 328, 352, 324, 346	24 months from date of mfg	Maintain < 80F
	226P	60 months form date of mfg	Maintain < 95F
	Rebar Coatings: 413	6 months from date of mfg	Maintain < 80F
413 SG, 426	12 months from date of mfg		
413/215	24 months from date of mfg		
OEM Powder Resins: 5555	18 months from date of mfg	Maintain < 70F	
260, 262, 263, 265	24 months from date of mfg	Maintain < 80F	
5230N, 5400	24 months from date of mfg	Maintain < 60F	